

# Hydrokleen Wastewater Filtration

## ACF3 - Multimedia Filtration

The ACF3 is designed for flow thru filtration rates up to 12 GPM and incorporates two (2) separate filtration modules. Each module incorporates a filtration media that is selected to assist with filtration or recycling requirements. Solids, oils & grease (hydrocarbons) or metals filtration, choose to solve any two (2) filtration requirements with the ACF3. Every Hydrokleen filtration systems that feature PLC operation can also incorporate pH control, bacteria, pathogen, odor elimination and more, along with remote system monitoring. Contact a Hydro Engineering, Inc. project manager for complete system design and application assistance.

### Standard Features

- Overflow Protection
- Gravity Flow Through Design
- Self-cleaning Tank
- Polishing Loop for Fine Solids
- Emulsified Oils, and Hydrocarbon Removal
- Polishing Loop for Metals and Chemical Removal
- PLC Controls

### Optional Features

- Service Indicator Beacon
- Logic Controller Inputs
- Remote Operation Monitoring
- Pressurized Discharge To Drain
- [Auto Dosing For Biological Odor Control and Hydrocarbon Elimination](#)
- [Auto Dosing For De-Foam](#)
- [pH Control](#)
- Ozone Bacteria Control
- Full System Vented Enclosure



### Specifications

Dimensions, Inches (cm) 142.5" (362) L X 37.5" (95.3) W X 75" (190.5) H  
Weight, Lbs (kg) 1466 (665)

	Standard
Volts (60Hz)	230V-1P
Amps (60Hz)	18

### Pricing

For complete pricing details,  
Submit a quote online below.

[Get a Quote](#)