

Hydrokleen Wastewater Filtration Bioreactor-C - Organic Waste Digester

Bioreactor-C wash water treatment system is designed to improve wash water quality for recycling back to wash processes or to meet requirements for sewer discharge. Systems are available with reaction tank sizes up to 2500 gallons.

The Bioreactor-C is high flow system designed to optimize the action of Hydro Biodigester product. It employs a moving reaction bed that consists of near neutral buoyancy bio-balls that provide colony locations for the Biodigester acteria. The system includes a high-volume pump and air injection that agitates the biomass and maintains a well-mixed aerated solution, which insures oxygen and food, are continuously available to the bacteria. Biodigesters are automatically metered into the tank to maintain high levels of beneficial enzymes and bacteria that are targeted at reducing oil, fuels, alcohol, soap, organic chemical, other bacteria, plant and food wastes in the waste stream. Hydrokleen filtration / recycling systems are UL-979 and CSA certified, and conform to CE standards.

Standard Features

High Flow Reaction Pumps
210 Gallon Bioreactor Tank
Gravity Flow Through Design
Pressurized Discharge to Process (Recycle)
Overflow Protection
Manual Sludge Drain
Sump Pump Discharge

Optional Features

50-Hz Motor
Control Panel Mounted Electrical Disconnect
UP to 4 High Flow Reaction Pumps
500, 1050, and Larger Bioreactor Tanks
Full System Enclosure
Power Ventilation
Biological Odor Control and Hydrocarbon Elimination
pH Controller
De-foam Control



Specifications

Flow Rate - GPM (LPM) 25 (94.6)
Dimensions, Inches (cm) 75" (190.5) L X 47" (119.4) W X 90" (228.6) H
Weight, Lbs (kg) 992 (418)

Pricing

For complete pricing details, Submit a quote online below.

Get a Quote







Hydrokleen Wastewater FiltrationBioreactor-C - Organic Waste Digester

Standard

Volts (60Hz)	230V-1P
Amps (60Hz)	12.5

Pricing

For complete pricing details, Submit a quote online below.

Get a Quote



